

PRODUCT: 5133



PRODUCT DESCRIPTION

Double-sided self-adhesive tape with polyester carrier, clear solvent acrylic adhesive.

LINER

65 gsm red two side siliconised MOPP

CARRIER

Clear PET

ADHESIVE

Clear solvent acrylic

MAIN APPLICATIONS

General purpose, especially used in furniture industry, gluing of profiles, automotive and the graphic arts.

FEATURES

Very aggressive adhesive, high tack, good cohesion, which is compatible with a wide range of materials.

TECHNICAL DATA (average values)

ELONGATION (AFERA 5004)	[%]	120
TENSILE STRENGTH (AFERA 5004)	[N/cm]	43
180° PEEL (AFERA 5001)	[N/25mm]	21
STATIC SHEAR (AFERA 5012)	[h]	>500
ROLLING BALL TACK (PSTC 6)	[cm]	<11
THICKNESS (AFERA 5006)	[μ]	190
THICKNESS LINER (AFERA 5006)	[μ]	70
PERFORMING TEMPERATURE	min -30 °C	max +180 °C

DATE: 01/09/16

The product has a shelf life of 12 months when stored in original packaging at a temperature of 21 °C with a relative humidity of 50%. BO.MA products were developed based on high quality standards to give good results even in difficult conditions, and are regularly subjected to stringent controls. All information and recommendations contained in our publications are the result of theoretical and practical experiences and provide the best of current knowledge. However, they do not involve any form of guarantee, either direct or implied, regarding the suitability of the product to a particular application, nor can they be considered as a basis for technical specifications. Therefore, determining whether the product BO.MA is appropriate for a specific application or technology is of the user's responsibility. It is therefore advisable to run tests in order to verify the suitability of the tape BO.MA chosen for your application and for the specific performance requirements. BO.MA engineers are always available to help.